

Product Datasheet

26-port Gigabit Ethernet Fiber Switch

(ONV-H3226F)



OVERVIEW

The ONV-H3226F is an unmanaged gigabit Ethernet fiber switch independently developed by ONV. It has 24*10/100/1000M RJ45 ports and 2*1000M SFP ports. The RJ45 and SFP combined interface can be unaffected by the transmission medium, realizing convenient connection and expansion of the network. The scheme of the large backplane and large cache switching chip is preferred to improve the forwarding rate of large files and effectively solve the problems of video freeze and picture loss in the high-definition surveillance environment. It is suitable for hotels, banks, campuses, factory quarters and small and medium-sized enterprises to establish a cost-effective network.

Unmanaged mode, plug and play, no configuration, simple and convenient to use.

FEATURE

■ Full gigabit rate, high-speed transmission

- ◇ A combination of Gigabit Ethernet port and Gigabit SFP port to meet the networking requirements of various scenarios.
- ◇ Support non-blocking wire-speed forwarding.
- ◇ Support full-duplex based on IEEE802.3x and half-duplex based on backpressure.

■ Stable and reliable

- ◇ CE, FCC, RoHS.
- ◇ Low power consumption, metal casing, the fan active cooling.
- ◇ Self-developed power supply, high redundancy design, providing a long term and stable power output.

■ Easy to operate

- ◇ Plug and play, no configuration, simple and convenient.
- ◇ The user-friendly panel, it can show the device status through the LED indicator of PWR, Link/Act.


TECHNICAL SPECIFICATION

Model	ONV-H3218F	ONV-H3226F
Interface Characteristics		
Fixed Port	16*10/100/1000Base-T RJ45 ports (Data) 2*1000Base-X uplink SFP fiber slot ports (Data)	24*10/100/1000Base-T RJ45 ports (Data) 2*1000Base-X uplink SFP fiber slot ports (Data)
Ethernet Port	10/100/1000Base-T auto-sensing, full/half duplex MDI/MDI-X self-adaption.	

Fiber Port	Gigabit SFP optical fiber interface, default matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)	
Optical Cable/ Distance	Multi-mode: 850nm /0 - 550M, single-mode: 1310nm/ 0 - 40KM, 1550nm /0- 120KM.	
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤100 meter) 1000BASE-T: Cat5e or later UTP(≤100 meter)	
Chip Parameter		
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T IEEE802.3u 100Base-TX, IEEE802.3ab 1000Base-TX IEEE802.3z 1000Base-X, IEEE802.3x	
Forwarding Mode	Store and Forward(Full Wire Speed)	
Switching Capacity	48Gbps (Non-blocking)	52Gbps (Non-blocking)
Forwarding Rate@64byte	26.78Mpps	38.69Mpps
MAC	8K	
Buffer Memory	4M	
LED Indicator	Power: PWR (green), Network:Link/Act(green)	
Power Supply		
Total PWR / Input Voltage	30W (100-240V)	
Power Consumption	Standby<7W, Full Load<16W	Standby<8W, Full Load<20W
Power Supply	Built-in power supply, AC100~240V 50-60Hz 0.56A	
Physical Parameter		
Operation TEMP / Humidity	-20~+55°C, 5%~90% RH Non condensing	
Storage TEMP /	-40~+75°C, 5%~95% RH Non condensing	


Humidity		
Dimension (L*W*H)	270*180*44.5mm	330*204*44mm
Net /Gross Weight	<1.2kg /<1.8kg	<2.1kg /<2.8kg
Installation	Desktop, wall mounted	
Certification & Warranty		
Lightning protection / protection level	Lightning protection: 2KV 8/20us; Protection level: IP30	
Certification	CCC,CE mark, commercial, CE/LVD EN60950,FCC Part 15 Class B; RoHS	
Warranty	1 year, lifelong maintenance	

DIMENSION



- A. Work indicator for RJ45 port B. Power indicator C. Work indicator for SFP port
 D. 24* 10/100/1000M RJ45 ports E. 2* 1000M uplink SFP ports

APPLICATION



ORDERING INFORMATION

Model	Description
ONV-H3218F	Unmanaged Ethernet fiber switch with 16*10/100/1000M RJ45 ports and 2*1000M SFP ports. Built-in 30W power supply.
ONV-H3226F	Unmanaged Ethernet fiber switch with 24*10/100/1000M RJ45 ports and 2*1000M SFP ports. Built-in 30W power supply.
ONV-H3226FU	Unmanaged Ethernet fiber switch with 24*10/100/1000M RJ45 ports and 2*1000M SFP ports. Built-in 30W power supply.

PACKING LIST

PACKING LIST	CONTENT	QTY	UNIT
	26-port gigabit Ethernet fiber switch	1	SET
	AC Power Cable	1	PC
	Mounting Kits	1	SET
	User Guide	1	PC
	Warranty Card	1	PC

OPTICAL MODULE INFORMATION

Product	Model	Description	Unit
1.25G Optical Module	ONV-2630	SFP optical module, 1.25G, multi mode dual fiber 850nm, transmission distance: 550m, LC interface, support DDM, hot plug and pull.	PC
	ONV-2632	SFP optical module, 1.25G, single-mode dual fiber 1310nm, transmission distance: 20km, LC interface, support DDM, hot plug and pull.	PC
	ONV-2612-T	SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, LC interface, support DDM, hot plug and pull.	PC
	ONV-2613-R	SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, LC interface, support DDM, hot plug and pull.	PC
	ONV-2612-T-S C	SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, SC interface, support DDM, hot plug and pull.	PC

	ONV-2613-R-S C	SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, SC interface, support DDM, hot plug and pull.	PC
Power Module	ONV-2633	1.25G SFP optical module transfers to 10/100/1000M RJ45 port.	PC

CONTACT US



OPTICAL NETWORK VIDEO TECHNOLOGIES (SHENZHEN) CO., LTD.

Tel: 0086-755-33376606

Fax: 0086-755-33376608

Email: onv@onv.com.cn

Website: www.onvcom.com

Zip: 518000

Headquarter Address: Room 1003, Block D, Terra Building, Futian District, Shenzhen, China

Factory Address: The 4-6th Floor, No. 59, Huaning Road, Xinwei Community, Dalang Street,

Longhua District, Shenzhen, China

