

DS-3WRU3X-H**AX300 Wi-Fi 6 High Gain USB Adapter**

- Elevate Your Connectivity with Wi-Fi 6
- Real 6dBi High Gain Antenna for Stronger Connection
- Compatible with Various Operating Systems
- Built-in driver, one-click setup

**DS-3WRU3X-H is a Wi-Fi 6 adapter with transmission speed up to 286Mbps, which fits securely into your computer and has no effect on the usage of neighboring ports. With a real 6dBi antenna, it sets a record high in signal transmission and reception distance, allowing you to receive wireless signal anywhere at home. It contains an internal driver, which completes*

**installation automatically once plugged into your computer without tedious installation steps.*


▪ Specification

General	
Product Dimensions (W × H × D)	48mm×20mm×8mm
Package Dimensions (W × H × D)	237mm×100mm×18mm
Net Weight	0.025 kg
Packing Method	Single pack
Packing List	Wireless USBAdapter × 1 Quick Start Guide × 1 Regulatory Compliance and Safety Information × 1
Working Temperature	0 °C to 40 °C (32 °F to 104 °F)
Working Humidity	10% to 90% RH non-condensing
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Storage Humidity	5% to 90% RH non-condensing
Max. Power Consumption	≤ 1.25 W
Gross Weight	0.062 kg
Wireless Parameter	
Max. Transmission Rate of Air Interface	≤ 300 Mbps 2.4 GHz: Up to 286Mbps
Wireless Standard	IEEE802.11ax/b/g/n
Working Frequency Band	2.4G
Transmitting Power	<20dBm (EIRP) <0.1W(EIRP)
Wireless Performance	1*1 MIMO supported
Receiving Sensitivity	2.4 GHz 11b-1M:-96dBm 11g-6M:-94dBm 11n-20M-MCS7:-75dBm 11n-40M-MCS7:-72dBm 11ax-HT20M-MCS9:-69dBm 11ax-HT40M-MCS9:-66dBm
Antenna	1*6dBi Antenna
Hardware Parameter	
Power Supply Method	USB
Software Function	
Application Function	Station Mode , Soft AP Mode
Security Mode	Default encryption mode: Mix WPA-PSK/WPA2-PSK WPA algorithm: TKIP
Supported Operating System	win7/10/11/linux

▪ Available Model

DS-3WRU3X-H(0-STD)

▪ Dimension



See Far, Go Further



www.hikvision.com
support@hikvision.com

